

AD-A236 579



2

A KEYBOARD FOR UNDERWATER PERFORMANCE ASSESSMENT BATTERY TESTING

**T. L. KELLY
R. BOOTH**

**DTIC
ELECTE
JUN 12 1991
S B D**

REPORT No. 90-25

91-01628



Approved for public release: distribution unlimited.

**NAVAL HEALTH RESEARCH CENTER
P.O. BOX 85122
SAN DIEGO, CALIFORNIA 92186-5122**

**NAVAL MEDICAL RESEARCH AND DEVELOPMENT COMMAND
BETHESDA, MARYLAND**



91 6 7 132

A KEYBOARD FOR UNDERWATER PERFORMANCE ASSESSMENT BATTERY TESTING

**Tamsin Lisa Kelly
Richard Booth**

**Naval Health Research Center
P. O. Box 85122
San Diego, California 92186-5122**

Report No, 90-25, supported by the Naval Medical Research and Development Command, Bethesda, Maryland, Department of the Navy, under Research Work Unit 1711319.B134 MM3P30.002-6005. The views presented in this paper are those of the authors and do not reflect official policy or position of the Department of the Navy, the Department of Defense, nor the United States Government. The equipment described in this report was constructed by Lockheed Engineering and Sciences Company - Marine Systems Program office.

Summary

The report discussed a keyboard developed for collecting performance data from subjects submerged underwater. The keyboard is waterproof and has a simplified four button format, allowing divers to enter responses without looking at the keyboard and while wearing diving gloves. A testing session is discribed and appropriate software techniques are suggested.



Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

Introduction

Cognitive function in divers submerged at various temperatures is of interest both in military and some civilian settings. Underwater cognitive testing has sometimes been done using waterproof paper and pencils (e.g., Bowen, 1968; Davis et al., 1975) or auditory problem presentation with manual signals for responses (e.g., Stang and Wiener, 1970). Some simple testing devices have been constructed (e.g.; Biersner, 1976; Stang and Wiener, 1970). At the other extreme, complex equipment, exactly simulating the underwater tasks of interest have been created (e.g., Vaughn and Anderson, 1973; Vaughn, 1977). However, none of these alternatives provide data which can be compared to results of the typical computer administered performance assessment batteries (PAB) most often used in laboratory studies. Baddeley et al. (1975) employed a device allowing recording of true or false responses to problems projected on a viewing screen placed at the observation port of a submersion tank. We describe here an underwater keyboard which allows computer administration of many typical PAB tasks in any submersion tank equipped with a window through which a computer screen can be displayed and viewed.

Equipment

The underwater keyboard is pictured in Figure 1. A simplified four button keyboard was chosen so that divers could manipulate two buttons with each thumb, with no need to look at the keyboard to find a specific button. A software technique to implement tasks involving more than four possible responses using only four buttons will be discussed later in this report.

The four button keyboard is made up of two two-button switch boxes (Daniel-Woodhead 2-button control, Part Number 4052). The Hypalon diaphragms which come with these switch boxes were used. The switches were placed parallel to each other with a one inch space between them and a specially machined single face plate of Detrin was used to tie the two switch boxes together. Screws pass through the faceplate and diaphragms into the switch boxes forming a water tight seal. The subject holds the keyboard with the switch boxes cupped in the palms and the fingers fitting into the gap between the

boxes. This hand position allows easy access to the two buttons on each side with the thumbs. As only the thumbs are used, gloves without fingers (i.e. mittens) are not a limitation. The keyboard can be held firmly in one position, and the subject does not need to look at the keyboard to find a button.

The switch boxes are filled with Dow Corning DC200 100c.s viscosity dielectric fluid to further assure water exclusion. Initially, 1000c.s viscosity fluid was used. However, the higher viscosity fluid caused irregular slowing of switch opening after button release, interfering with measurement of response times in rapid sequential tasks. Changing to the lower viscosity fluid solved this problem.

Each switch boxes is connected to a 20 foot two conductor Hypalon jacketed underwater cable (Belden Wire and Cable, Belden 8424 QJ). The two cables are joined together at one foot intervals with shrink tubing to improve handling.

The wiring diagram is shown in Figure 2. These keyboards currently are used with Apple IIe computers for cognitive testing, but could easily be adapted for an IBM compatible type PC. To input data from this keyboard to the Apple IIe computers we use the powerful I/O 32 board manufactured by Applied Engineering. This four button underwater keyboard uses only a small portion of the boards capacity. The cable is connected to the I/O 32 board via a 25-pin connector (mated set), a 26-conductor ribbon cable (Warwick) and a 26-pin connector.

Testing

The keyboard was tested by a diver in a 3FFW, using open circuit SCUBA, wearing a dry suit (Viking Combat Swimmer Dry Suit, Model #3030). Two divers gloves manufactured by Divers Unlimited Inc., San Diego, California, were tested with the keyboard, a 5-finger, 1/8 inch neoprene glove (Model GWA-L) and an outer 3-finger, retractable mit of 1/4 inch neoprene (Model GD3FMR-L). The keyboard was manipulated easily with both gloves.

The presentations were in 40-column mode (characters 50 mm high). The screen was 3 inches outside the dive tank window and the divers face mask was 12-18 inches inside the window. The dive subject had 20/40 uncorrected vision and had no difficulty reading the screen. Since Navy divers are required to have 20/20 vision initially, it is anticipated that most of them should have no difficulty working with this apparatus.

Software Techniques

Some potential applications for this keyboard are straight forward, such as simple response times, choice reaction times with no more than four possible choices, logical reasoning or any other type of problem or question allowing four or fewer types of response. However, its use is not limited to these situations. Performance assessment batteries often include questionnaires with more than 4 possible answers to a given question. It is possible to modify such software to function with this keyboard by using a visual analog scale presentation. An example of such a presentation is diagrammed in Figure 3. This figure presents one question from the Naval Health Research Center Profile of Mood States Scale, in original and visual analogue scale formats. This scale consists of a series of words reflecting various moods. The subject responds to each word by stating how much it applies to his/her present mood on a scale of zero to four. In the visual analog scale set up, the subject is presented with a scale from zero to four, with a pointer sitting at the midpoint "2". To respond, the two upper buttons are used to move the pointer right or left, as appropriate. The right lower button is then pushed to register the answer.

Some types of tasks are difficult or impossible to set up on a keyboard with only four buttons. Mathematical calculations cannot be performed except with a multiple choice or odd/even type answer format. Digit symbol substitution could conceivably be set up on a sliding scale format. However, it would be cumbersome and very slow, and the display would be somewhat complex given the visual limitations of a subject looking through the air-water interfaces of a mask, water, and a glass window.

For users of Apple hardware, it should be mentioned that clock boards which use interrupts for timing small intervals (e.g., Timemaster II H.O., by Applied Engineering) require special programming to work with the I/O 32 board. If the boards are accessed directly from Apple Basic with the clock in the interrupt mode (the only mode in which the Timemaster II H.O. measures time in units smaller than 1 second) the system will freeze up. This problem can be solved by using an assembly language program to access the I/O 32 board and the clock. An assembly language program which facilitates the combination of the I/O 32 board and the Timemaster II H.O. used in conjunction with Applied Engineering's BIN.MILLISEC assembly routines (Applied Engineering, 1988) is presented in the Appendix. This program will work with either the enhanced or the unenhanced version of the Apple IIe.

REFERENCES

- Applied Engineering (1988) Timemaster II H.O. User's Manual. Applied Engineering, Carrollton, Texas.
- Baddeley, A.D., Cuccaro, W.J., Egstrom, G.H., Weltman, F., and Willis, M.A. (1975) Cognitive efficiency of divers working in cold water. Human Factors 17:446-454.
- Biersner, R.J. (1976) Motor and cognitive effects of cold water immersion under hyperbaric conditions. Human Factors 18:299-304.
- Bowen, H.M. (1968) Divers performance and the effects of cold. Human Factors 10:445-464.
- Davis, F.M., Baddeley, A.D., and Hancock, T.R. (1975) Diver performance: the effect of cold. Undersea Biomedical Research 2:195-213.
- Stang, P.R. and Wiener, E.L. (1970) Diver performance in cold water. Human Factors 12:391-399.
- Vaughn, W.S. Jr. (1977) Distraction effects of cold water on performance of higher-order tasks. Undersea Biomedical Research 4:103-116.
- Vaughan, W.S., Jr. and Anderson, B.G. (1973) Effects of long-duration cold exposure on performance of tasks in naval inshore warfare operations. Technical Report prepared by Oceanautics, Inc., Landover, Maryland, for Engineering Psychology Programs, Psychological Sciences Division, Office of Naval Research.

**APPENDIX: ASSEMBLY LANGUAGE PROGRAM TO RUN I/O 32 AND TIMEMASTER II H.O.,
IN CONJUNCTION WITH BIN.MILLISEC ROUTINE** RICHARD BOOTH 1989**

BUTTON SET ROUTINE

```
          LDX    #$20          ;load slot number
1$:      LDA    $C084,X        ;read Port A* bits
          BEQ    1$            ;if none set, check again
          STA    $3B0          ;return port A contents - PEEK(944)
          RTS                 ;done
```

BUTTON CLEAR ROUTINE

```
          SEI                 ;disable interrupts
          LDX    #$20          ;load slot number
2$:      LDA    $C084,X        ;read Port A* bits
          BNE    2$            ;if any set, check again
3$:      STA    $3B0          ;return port A* contents - PEEK(944)
          RTS                 ;done
```

ENTRY POINTS

CALL 945 invokes "button set" routine

X=PEEK (944) returns Port A* contents stored by most recent call
to "button set" or "button clear" routines

CALL 956 invokes "button clear" routine and disables timing
interrupts

CALL 957 invokes "button clear" routine but permits
interrupts and response timing to continue

APPLE BASIC CODE TO ENTER THIS ASSEMBLY LANGUAGE

```
NN=945
FOR M=0 TO 22: READ X: POKE NN + M, X: NEXT M
DATA 162,32,189,132,192,240,251,141 176,3,96,120
DATA 162,32,189,132,192,208,251,141 176,3,96
```

* The keyboard is connected to Port A on the I/O 32 board. A button

press sets the corresponding Port A bit, button release clears it.

** Applied Engineering assembly language program.



FIGURE 1. UNDERWATER KEYBOARD




Figure 2. Wiring diagram for underwater keyboard

A)


FRIENDLY

0=NOT AT ALL
1=A LITTLE
2=MODERATELY
3=QUITE A BIT
4=EXTREMELY

B)

0=NOT AT ALL
1=A LITTLE
2=MODERATELY
3=QUITE A BIT
4=EXTREMELY

FRIENDLY



USE UPPER KEYS TO MOVE POINTER
PRESS LOWER RIGHT KEY TO ACCEPT

Figure 3. Formats for Profile of Mood States questions:
A) standard keyboard format; B) four-button
keyboard format.

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS N/A	
2a. SECURITY CLASSIFICATION AUTHORITY N/A			3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.	
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A			5. MONITORING ORGANIZATION REPORT NUMBER(S)	
4. PERFORMING ORGANIZATION REPORT NUMBER(S) Report No. 90-25				
6a. NAME OF PERFORMING ORGANIZATION Naval Health Research Center		6b. OFFICE SYMBOL (If applicable) Code 50	7a. NAME OF MONITORING ORGANIZATION Chief, Bureau of Medicine and Surgery	
6c. ADDRESS (City, State, and ZIP Code) P. O. Box 85122 San Diego, CA 92186-5122			7b. ADDRESS (City, State, and ZIP Code) Navy Department Washington, DC 20372-5120	
8a. NAME OF FUNDING/SPONSORING ORGANIZATION Naval Medical Research & Development Command		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code) NNMC Bethesda, MD 20889-5044			10. SOURCE OF FUNDING NUMBERS	
			PROGRAM ELEMENT NO. 62233N	PROJECT NO. MM3P30
			TASK NO. 002	WORK UNIT ACCESSION NO. DN246548
11. TITLE (Include Security Classification) (U) A KEYBOARD FOR UNDERWATER PERFORMANCE ASSESSMENT BATTERY TESTING				
12. PERSONAL AUTHOR(S) TAMSIN L. KELLY AND RICHARD BOOTH				
13a. TYPE OF REPORT Interim		13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 901108	15. PAGE COUNT
16. SUPPLEMENTARY NOTATION				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Diving; Cognitive performance; Computer; Keyboard	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)				
<p>A waterproof keyboard has been developed. This allows collection of cognitive performance data from divers submerged in a tank. Cognitive tasks are presented to the divers on a computer screen placed at the tank viewing window. The four button keyboard can be easily manipulated while wearing standard diving gloves. Software techniques for adapting various types of tasks to the four-button response format are discussed.</p>				
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input checked="" type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified	
22a. NAME OF RESPONSIBLE INDIVIDUAL Tamsin L. Kelly			22b. TELEPHONE (Include Area Code) (619) 532-6114	22c. OFFICE SYMBOL 50